

COMPLETE



PROFIX ESSENTIALS



Pro-Grip Assurance

All our products are marked with the relevant standard icon where applicable and certified to all relevant standards.

1000v Safe

Our range of ProFix tools for safe 1000v working. Any ProFix tool carrying the VDE logo is also guaranteed to this standard.

Pro-Save

All our kits offer substantial savings over the purchase of individual items, representing even greater ProFix value.

Pro-Safe First

The ProFix Safety First Pro-Safe symbol serves as a reminder to all our customers to always ensure you use the correct safety equipment whilst working. Do not risk injury!

PROFIX ESSENTIALS

The Pro-Fix Brand is aptly named Pro-Fix Essentials as it includes an array of mainly secondary but fundamental products needed on a day to day basis by electrical contractors. Insulated and general hand tools comprise a key element of the range - from VDE pliers, cutters, strippers and screwdrivers to general crimping and tensioning tools plus a whole gamut of hand tools, sealants and drills. Fastenings account for the second half of the Pro-Fix portfolio with cable clips, cleats, shrouds, crimps and ties key everyday products. Earthing, sleeving and grommets are also well covered as are screws, anchors and washers. Finally more mainline electrical meters and testers complete the Pro-Fix Brand.



We have a team of friendly, experienced and dedicated personnel ready to provide you with a high quality service.

We continue to trade solely through the electrica wholesale trade, and we would like to remind our customers should you require any help or assistance, our dedicated sales staff will be glad to help.



We now have Price List 20 available in Excel format for customers who require it to update databases etc. Please contact us for your copy.

All information shown in this catalogue is correct at time of going to press, however we reserve the right to alter or amend the data without prior notice. If you are in doubt please ask our sales team for assistance before ordering.

PRŒIX

ESSENTIALS

Pro-Grip Professional

- All VDE pliers are tested in accordance with IEC DIB EN 60900 and live up to 1000v
- High grade carbon steel
- Finger stops to prevent slipping
- Heavy duty insulation on hand grip
- Pro-Grip provide extra comfort for less hand
- All products are quality guaranteed and manufactured to the







Pro-Grip

Pro-Safe

INSULATED TOOLS

Pro-Grip Professional - Pliers & Cutters



Code: TLSC6MF

Side Cutter 6" Multi-Function 1.5 & 2.5mm²

- Diagonal insulation cutter & stripper
- High pivot point for greater leverage Wire stripper notches 1.5 & 2.5mm²
- Drop forged and heat treated
- Finish Polished chrome head

GS (F

ength.	Cutting Capacity	BoxQty 1/6	Each
60mm	1.5 - 2.5mm ²	M00: 1	









High leverage combination pliers

- Chrome Vanadium steel.
- drop forged & heat treated
- Induction Hardened cutting edge
- Finish Polished chrome


€ (€	
Length	Cutting Capacity
200mm	3mm ²





Finish - Polished chrome

A CE











36.13(cbm)

54.91(dB)





Pro-Safe safety first

INSULATED TOOLS

Pro-Grip Professional - VDE Electricians 9 Piece Tool Kit

Code: TLETK9VDE

9 Piece Electricians Tool Kit - Professional

1000V VDE (approved)

TOUGH ADE (approved)

Ideal for professional electricians

Pro-Grip composite handles for ultimate comfort and control

Finger stops to prevent slipping on to live conductors

High quality machined pivots for easy one handed operation

Manufactured to stringent quality standards and quality guaranteed

Supplied in robust zip-up tool case

◆ VDE Slot He
◆ VDE Slot He
◆ VDE Slot He
◆ GS / Neon To
◆ VDE Pozi He
◆ VDE Pozi He

VDE Long Nose VDE Side Cutte

JUI Case		
	Tip Size (mm)	Blade Length (mm)
ad	1.5 x 5	125
ad	0.8 x 4	100
ad	0.4 x 2.5	75
ester	0.28 x 3	65
ad	PZ1	80
ad	PZ2	100
	Volts	Length (mm)
on Pliers	1000v	200
Pliers	1000v	200
re	1000v	160

 Length
 Width
 Depth

 264mm
 236mm
 63mm

Weight 1.37Kg BoxQty 1 Each

Pro-Save

€ CE

All our kits offer substantial savings over the purchase of individual items, representing even greater ProFix value.



Pro-Grip assured



TOP SELLING

Pro-Grip Professional - VDE Professional 7 Piece Screwdriver Set Kit

Code: TLVDE7

7 Piece Screwdriver Set - Professional



Ergonomic handles with anti-skid protection

Combined with high quality blades made of special alloys

Fully insulated screwdrivers guarantee maximum user safety for live working

Includes mains tester

Packaging - Widowed display pack (2 colour Box)

Colour - Red Handle & Black Blade

Screwdrivers VDE Slot Head VDE Slot Head VDE Slot Head VDE Slot Head GS / Neon Tester VDE Pillios Head

VDE Pillips Head

Tip Size (mm)	Blade Length (mm)
1.25 x 6.5	150
1 x 5.5	125
0.85 x 4	100
0.4 x 2.5	75
0.4 x 3	65
PH2	100
PH1	80

Kit contains:-4Pcs Slotted Blade Screwdrivers DIN5265 2Pcs Philips Blade Screwdrivers DIN5260 1Pc Neon Tester 220-250v DIN0860



Length	Width	Depth
340mm	85mm	35mm

Weight	
583g	

BoxQty 1/30	Each
M00: 1	



INSULATED TOOLS

Pro-Grip - Standard - Pliers, Side Cutters & Strippers



Pro-Safe

Pro-Grip Standard TÜV/GS (approved)

- Chrome vanadium material
- Handle material PVC with polished chrome finish
- Finger stops to prevent slipping
- Contoured anti-slip shoulders for ease of use and safety
- Packing Card hanger

Code: TLSC6 Side Cutter - Standard

Suitable for medium hard wire cable

- · Heavy duty two colour insulation on hand grip
- Head and jaws configuration gives high leverage and ease of use







Code: TLWS6

Wire Stripper - Standard

- Coil spring brass adjustment screw and locknut
- Strips cable size 0.3 5mm
- Heavy duty fully insulated hand grip

TUV 65 (E

Length	Cutting Capacity
160mm	0.3 - 5mm ²








	4	D 0: 4/0
Length	Cutting Capacity	BoxQty 1/6
200mm	3mm²	M00: 1






INSULATED TOOLS

VDE Tools - Pliers, Side Cutters & Strippers





Code: CC60
Cable Cutter 8" (Heavy Duty)

Red PVC ergonomic non-slip handles
Induction hardened cutting edges
Suitable aluminium, copper and plastic sheathed cable
Not suitable for steel wire

Arroy

Length
Cutting Capacity
235mm
up to 60mm²
MOQ: 1

WHERE CAN I BUY MERIDIAN, AXIOM, AIRMASTER & PROFIX BRANDED PRODUCTS?

Our products are usually in stock at all good electrical wholesalers. For a local one please call our sales team they will be happy direct you. Or contact our regional sales manager covering your area, they will be happy to help you find a local stockist.

FOR <u>ASM</u> CONTACT DETAILS SEE INTRODUCTION OF THIS PUBLICATION

PROFIX

ESSENTIALS

Pro-Grip - Screwdrivers

 Pro-Grip blades are manufactured from special high grade Chrome-Vanadium-Molybdenum-Steel alloy (Black finish) and are carefully hardened to provide maximum durability

Pro-Grip screwdrivers go through 100% inspection and strict production and control procedures to guarantee the highest precision for trouble free and safe working

 An ergonomically designed two component handle with micro antislip surface ensures easy grip and provides maximum torque (up to 50% more power transmission over some mono-component screwdrivers)

 Pro-Grip have their insulation injection-molded directly around the blade for live working up to AC 1000V complete with handy hole for hanging/ storage







Pro-Grip assured

Pro-Safe safety first







Electricians Screwdrivers - Heavy Duty

				Dimensions (mm)				
		Code	Type	Overall Length	Blade Length	Tip Size	Box/Qty	Each
	Α	TLS253VDE	Slotted	155	75	0.4 x 2.5	10	
	В	TLS34VDE	Slotted	180	100	0.5 x 3	10	
	С	TLS44VDE	Slotted	190	100	0.8 x 4	10	
	D	TLS555VDE	Slotted	225	125	1 x 5.5	10	
	Ε	TLS656VDE	Slotted	260	150	1.2 x 6.5	10	
(F	TLSPH1VDE	PH	180	80	No. 1	10	
T	G	TLSPH2VDE	PH	210	100	No. 2	10	



VDE/GS approved 1000v range of top quality insulated screwdrivers for professionals



PRŒIX ESSENTIALS





INSULATED TOOLS

VDE Tools - Pliers, Side Cutters & Strippers



Code: TLNTSF Mains Neon Tester - Small Voltage 220-250v AC Chrome plated flat tip

 Used for terminal screws With pocket clip Used for terminal screws

 With pocket clip TUV &S (6

man annu				
		BoxQtv 10/250	F	100 -
Length	Blade/Tip Size	DUXULY 10/200	Each	100+
140mm	65 x 3mm ²	M0Q: 10		



Code: TLPSS

Precision Screwdriver Set Hardened & tempered steel

Slotted screwdriver 1.4, 2, 2.4, 3mm

Phillips 0 and 1

Plastic storage box with hinged lid



-			
Length	Width	Depth	
105mm	70mm	10mm	







Manufactured from high speed steel

For use with tap wrench to clear blocked threads

Use M4 for electrical conduit boxes

$C \in$			4g
Thread	Full Length	BoxQty 1/10	Each
		M00: 1	
15mm	54mm	MUU: I	

Code: TWT

Tap Wrench Type 'T' M3.5 & M4 - Adjustable Manufactured from high quality steel

Adjustable ratchet tap wrench M3-M4

 Used with taps M3.5/M4 for re-cutting damaged or badly formed threads in electrical boxes



Code: TLRT35 & TLRT4

M3.5 & M4 Re-Threader for Circular & Switch & Socket Boxes Manufactured from high speed

steel with precision ground threads Ergonomically designed grip for comfortable and safe use Used for re-cutting damaged

or badly formed thread in electrical conduit boxes



ϵ			4g
Thread	Diameter	BoxQty 1	Each
80mm	Ø18mm	M00: 1	

CE					24g
Code	Thread	Full Length	Box/Qty	Each	
TLRT35	3.5mm ²	110mm	1/20		
TLRT4	4mm ²	110mm	1/20		
				Minimum order e	wontity 1

PROFIX

ESSENTIALS

Features & Benefits

- · Crimping produces a reliable connection between conductor and contact
- Small size tools for pre-insulated lugs up to 6mm²
- . Large size tools for copper lugs up to 125mm²
- DP Series for data products







GENERAL TOOLS

Pro-Grip - Crimpers / Modular Plug & Data Cable Tools



Code: CPT25/150 Crimping Tool - Heavy Duty

- Hex crimping tool for non-insulated terminals
- High quality crimp tool for terminating copper tube terminals 25-150mm
- Die sets revolve within the tool head for quick and easy selection
- Heavy duty steel bar type handle with strong rubber grip









		BoxQtv 1/10	Fools
Lenath	Terminals	DUXULY 1/10	Each
220	0.5(0(1	M00: 1	
230mm	0.5mm/6mm (Insulated)	10104. 1	



 Crimps 1.5/2.5/6mm Shears M2.6/M3/M3.5/M4/M5 Screws







Length	Capacity	BoxQty 1/10	Each
230mm	1.5-6mm ²	M00: 1	

ESSENTIALS





Pro-Safe

GENERAL TOOLS

Pro-Grip - Crimpers / Modular Plug & Data Cable Tools

Code: CPT6/25

Code: DPPDT1

Punch Down Tool - Plastic









		BoxQtv 1	F
Length	Capacity	BOXULY I	Each
635mm	10-95mm ²	M0Q: 1	











Length	Range	BoxQty 1/10	Each
165mm	2.4-4.8 (wide)	M00: 1	

CAN I COLLECT ORDERS?



ESSENTIALS





Pro-Grip - Crimpers / Modular Plug & Data Cable Tools







LAN Modular Cable Tester Kit/Device Status Identifier

- 5 in 1 Cable Tester
- New ergonomically portable hand held design
- Easily read pin configuration of RJ45/RJ11, USB and BNC cable
- Visible LED pin/wires status display



Length	Width	Depth
185mm	100mm	25mm


 $(\epsilon$

BoxQty 1 Each
MOQ: 1

Code: CTT96

Cable Tie Tool up to 9.6mm

- Strong Steel body
- Pulling force adjustable
- Cuts automatically when set force is reached
- Works on Cable Tie widths upto 9.6mm (maximum)





Code: PTLPC PVC Pipe Cutter

- Ratchet action
- Diecast Aluminium body





Length	Size	BoxQty 1	Each
190mm	42mm (max.)	M00: 1	

CAN I HAVE AN ACCOUNT?

Yes - If you are a wholesaler then please visit our website and download an account application form and email it to us. Please ensure you read our terms & conditions contained at the end of Technical Information section of this publication.

We supply the electrical wholesale trade exclusively









GENERAL TOOLS

Spanners, Measures & Bolsters

Our full range of tools are designed to be incredibly robust and excellent quality

Code: TLAS8 Adjustable Spanner 8"

- Professional quality alloy steel
- Satin Chrome Finish
- Super Smooth Action
- Clip display card packing with Euro hook
- Available Sizes 6" 12"
- Laser marked graduation on the jaws

Overall Length	Jaw Capacity
200mm	25mm



M00: 1



Length 205mm

	BoxQty 1	Foob
Size	DUXULY I	Each
20/25mm	M00·1	
20/2311111	10100. 1	

Code: TLEP Electrician Pouch

Double pouch tool belt with 11 pockets

- Suede leather material
- 50mm webbing belt
- 2 hammer loops, tape holder, pliers pouch

Pov0ty 1/10	
Length Width BoxQty 1/10	
300mm 200mm MOQ: 1	

Code: TLTM10 Tape Measure 10Mtr - Heavy Duty

- Heavy tape with soft grip with impact resistant case
- Metric and imperial graduations
- Blade lock with automatic return

10lVltr lo	ng and 32m	ım wide			
					520g
			BoxQty 1/6		
Length	Width		DUXULY 1/0	Each	1
10m	32mm		M0Q: 1		

		CE
		520g
BoxQty 1/6	Each	
M00: 1		

TOP SELLING

Code: TLTM5 Tape Measure 5Mtr/16ft

- High quality tape with quality shock-proof rubber housing Clear and easy to read metric
- and imperial graduations Easy to lock button with
- smooth power spring return 5Mtr long and 19mm wide

Length	Width
5m	10mm



CE

600a

Each

BoxQty 1/10	Each
M00: 1	

Code: TLBL2 Bolster 2.25" with Grip

- Solid forged from quality Steel Heavy duty plastic hand guard
- for extra safety and shock absorption Hardened cutting edges
- Suitable for use on bricks

Length	Width
220mm	57mm



Code: TLBL4 Bolster 4" with Grip

- Hard forged quality Steel Strong flexible hand guard
- for safety Hardened cutting edges
- Ideal for use by electricians

Length	Width
220mm	100mm





PRŒIX

ESSENTIALS





GENERAL TOOLS

Chalk Reels & Hex Keys

Code: TLCLR Chalk Line Reel

- Light weight durable casing Large screw-top filler cap
- Can be used as a plumb bob
- Fold away winding handle
- 30Mtr of cotton line

 $(\epsilon$

Length Size 110mm 30m



M00: 1

Code: TLCLRCHK Spare Marking Chalk

- Micro fine quality chalk
- Contained in an airtight plastic container with pouring spout
- Replacement chalk for TLCLR

(6

Colour Red or Blue



BoxQtv 1 Each M00: 1

Code: TLHEX25

Hex Key Set 25pcs - Long Series

- Chrome Vanadium Steel
- 25 piece metric and imperial Hex Key Set (long series)
- Easy access to Hex screws in confined spaces







BoxQty 1	Each
M00: 1	

Code: TLHEX7

Hex Key Set 7pcs

- Chrome Vanadium material 7 piece metric Jack Knife Hex
- with rigid plastic handle
- 2.5-10mm range



. C	
Length	Cutting Capacit
200mm	2mm?




BoxQty 1/6 Each M00: 1

Code: TLBHEX7

Hex Ball End Key Set 7pcs

- Chrome Vanadium material 7 piece metric Hex Key
- Ball End Set Hex Key sizes 2.5-10mm
- in storage clip







BoxQty 1	Each
M00: 1	

Code: TLMK

Hex Key Multi-Purpose - Four Way

- Multi-purpose 4 way key -
- Electric/Gas/Water cupboard
- n Perfect for maintenance work
- n Made from Diecast Zinc





BoxQty 1	Each
M00: 1	

PRŒFI ESSENTIALS





Pro-Safe

GENERAL TOOLS

Hand Tackers & Saws

Code: TLCT45 Hand Tacker Regur 45 GPO/ALARM

- Regur Cable Tacker and multi-purpose Staple Gun in one
- Steel construction, outer PVC/Steel
- Soft recoil free trigger to load staple





y 1	Each
: 1	

Code: TLCTS10 Cable Staples 10mm

- Staples for TLCT45
- Size 10mm
- Finish Galvanised



BoxQty 5000	Each
M00: 1	

Code: TLPS Dry Wall Saw

Blade

150mm

180mm

- Hard point plasterboard saw Large comfortable soft grip handle Extra sharp teeth and pointed
- end for piercing plasterboard

Width

15mm

8

 Ideal for fitting sockets and downlighters



		CE
A CONTRACTOR OF THE PARTY OF TH		149g
BoxQty 1/6	Each	
Mnn· 1		

Code: TLHSL

10mm / 3/8"

Hacksaw 10/12" Adjustable - Large

- Strong beam keeps blade rigid
- Hand grip designed for comfort and protection
- Supplied with high grade metal blade
- Tough shock absorbing back providing high break resistance



Blade	Width	TPI	BoxQty 1/10	Each
300mm	125mm	24	M00: 1	

Code: TLHSM Hacksaw Medium Size

- Adjustable blade tension for cutting metal or wood
- Strong Aluminium frame



M00: 1

BoxQty 1/10 Each

Code: TLHSJ	
Hacksaw Junior	

Quality spring steel construction

- Long life spring steel frame
- Handy size to reach awkward places



Blade	Width	TPI	BoxQty 1/10	Each
240mm	65mm	32	M00: 1	

Code: TLHSLB

Blade

260mm


- Blades 12" 24T Large HSS bi-metal flexible blade
- High speed steel teeth welded to top quality carbon steel backing

Width

80mm

 Provides superior cutting efficiency with maximum safety

Width	TPI
15mm	24



16g

Code: TLHSJB

150mm

Hacksaw Junior Blades

- Top quality general purpose metal cutting blades with pinned end to fit standard junior hacksaw frames
- Packed in quantities of 10

Width

10mm

TPI

32



BoxQty 10/100	Each
M00: 1	







GENERAL TOOLS

Silicon Sealants

Code: TLSSGUN Silicon Sealant Gun

- Hexagonal rod with hooked end
- Easy pull trigger
- Heavy duty

(€ 300g

Length	Width	Depth	Вс
280mm	48mm	300mm	

BoxQty 1/10 Each
MOQ: 1

Code: TLSSWHI

Silicon Sealant 300ml Cartridge (White)

 Waterproof Sealant suitable for both interior and exterior use

 Provides an excellent bond to glass, metals, ceramics, most plastics and contains an antifungal compound to prevent mould growth when used in high humidity areas

Canacity

300ml

s, metals, ins an anti-d growth when

336g

BoxQty 1/25

Each

Silicon Sealant 300ml Cartridge (Clear)

Waterproof Sealant suitable for both interior and exterior use

 Provides an excellent bond to glass, metals, ceramics, most plastics and contains an antifungal compound to prevent mould growth when used in high humidity areas

Marie Contraction of the Contrac) (e
	336g

Lenath	Width	Capacity	BoxQty 1/25	Each
210mm	45mm	300ml	M00: 1	

Code: TLACS

Lenath

210mm

Acrylic Sealant/filler Cartridge Paintable

Width

45mm

- Multi-use product that seals, bonds, caulks, covers, protects, insulates and waterproofs
- Ideally suited for the sealing and filling of joints and cracks where movement can occur such as plaster-work, window frames, door frames, skirting boards and architraves

M00: 1

- · Good adhesion on plastic, wood, brick, stone, aluminium, glass and ceramic tiling
- Suitable for both interior and exterior use

Length	Width	Depth
210mm	45mm	300mm



BoxQty 1/25	Each
M00: 1	

 $(\epsilon$







GENERAL TOOLS

Hammers, Wood Chisels and Knives



Club Hammer 21/2lbs Wooden Handle

Drop forged steel head

 Ideal for heavy duty and general purpose use



Length	Width
230mm	90mm

_	
BoxQty 1/6	Each
M00: 1	

Code: TLCLH

Claw Hammer 16oz Steel Shaft

Fibreglass handle for maximum strength

Drop forged carbon steel head

Shock absorbing rubber grip



Length	Width	BoxQty 1/5	Each
330mm	130mm	M0Q: 1	

Code: TLCW4SET

Chisel Set 4 Pieces Wood Soft Grip

- 4 piece set consisting expert quality hardened steel bevel edged blades
- Cushion grip 2 piece handle with steel striking cap
- Chisels can be struck with hammer or mallet



BoxQty 1	E
M00: 1	

Code: TLSI Soldering Iron 25W

- General purpose soldering iron suitable for electrical work on small to medium wires and cables
- BS approved 13A plug 230v/AC



Length	Watts	BoxQty 1/10	Each
220mm	25	M0Q: 1	

Code: TLSOL

Solder Dispenser 12pcs Carded Solder 40/60 alloy - lead free

Pack of 12 pieces

Size

6,13,19,25mm



PCS: 12	Each
M00: 1	

Code: TLKHD

Heavy Duty Retractable Utility Knife Heavy duty Diecast construction

- Adjustable for depth of cut
- Rubber inserts for secure grip Includes heavy duty blade
- Display packaging

Length	Width
1 - 0	20



BoxQty 1/10	Each
M00: 1	

Length 95mm 20mm

Code: TLKBL Knife Blades for TLKHD Heavy duty 0.6mm blades in

- dispenser (10) Size 58mm x 19mm
- Blades fit TLKHD

Length	Width
58mm	19mm



BoxQty 10/100	Each
M00: 1	

Code: SP8054

Joist Guard Galvanised finish

- Provides protection for cables threaded through joists during electrical rewiring works
- Robust construction for extra cable safety
- Fast and easy installation

Length	Width
80mm	54mm



BoxQty 100	Each
M00: 1	



PRGFIX

ESSENTIALS

GENERAL TOOLS

Pyro Tools

JOI Stripper -

ZSJ for stripping cable sheath on popular .sizes 2L1, 2L1.5, 2L2.5, 3L1, 4L1, 4L1.5 Spare blade - ZSJB

Small Pyro Stripper -

ZSUS for stripping cable Spare blade - ZSUSB

Large Pyro Stripper -

ZSU for stripping cable Spare Blade - ZSUB

Pyro Ringer -

ZR this tool is used to assist the removal of sheath at a selected point and is used in conjunction with side cutter

Pyro Pot Wrench -

ZPM20, ZPM25 Size - 20mm & 25mm used in conjunction with cable gland to screw on brass pot

Pvro Crimper -

ZDC20. ZDC25 Size 20mm & 25mm used for a quick method of crimping the mouth of the pot to secure the closure



	Code	Description	Box/Qty	Each
Α	ZSJ	JOI Stripper	1/10	
	ZSJB	Spare Blade for ZSJ	1/10	
В	ZSUS	Small Pyro Rotary Stripper	1/10	
	ZSUSB	Blade for ZSUS	1/10	
С	ZSU	Large Pyro Rotary Stripper	1/10	
	ZSUB	Spare Blade for ZSU	1/10	
D	ZR	Pyro Ringer	1/10	
Е	ZPM20	Pyro Easy Pot Wrench 20mm	1/10	
F	ZPM25	Pyro Easy Pot Wrench 25mm	1/10	
G	ZDC20	Pyro Hand Crimp 20mm	1/10	
Н	ZDC25	Pyro Crimp 25mm	1/10	

GENERAL TOOLS

Draw Tapes Metal & Nylon

- Rugged easy to use hardened tempered steel draw tape
- Casing High impact resistant Nylon Polyamide for durability and heavy use, helps protect tape and saves time in keeping kink free
- Compact easy grip handle, lets you turn reel in either direction for one hand feed or take up while other hand directs tape or bring it back tightly

Draw Tape Steel - Retractable

Equipped with durable plastic container and side handle

Code	Length	Width	Thickness	Weight	Box/Qty	Each
H1130	30m	3mm	1.5mm	1900g	1/10	

Draw Tape Nylon

- Strong Nylon draw-in tape (3mm diameter)
- Strong Brass head
- Available in 10/20/30Mtrs
- Colour:- Clear



Code	Length	Width	Thickness	Weight	Box/Qty	Each
DT10	10m	3mm	-	88g	1/10	
DT20	20m	3mm	-	253g	1/10	
DT30	30m	3mm	-	270g	1/10	

Code: DTGEL

Cable Drawing Yellow Gel Slot

- Dries slowly to a thin nonconducting film that won't harden in conduit
- Safe to use with all cable types
- Poly-tetra-fluoroethylene additive provides greater lubricity than other wax-based lubricants

Capacity
950ml



(€ 1012g

BoxΩty 1 Each MOΩ: 1





Pro-Safe

DRILLING TOOLS

Mandrel / Hole Saws & Pilot Drills

- Bi-metal construction Variable pitch 4/6 per inch
- Long life fast and smooth cut with shock resistant teeth
- Cuts hole in wood, plastic, machinable metal, pipe & stainless steel
- Cutting Depth up to 40mm
- Heavy duty bi-metal construction for durability
- Hole Saws/Arbors interchangeable with other brands
- Cuts Brass, Copper, Steel, Aluminium, Wood etc.
- M3 steel cutting edge keeps teeth sharper longer



ot	

Code	Туре	Overall Length	Mandrel Size (mm)	Weight	Box/Qty	Each
TLPDL	Large	120mm	MN152	-	1/50	
TLPD	Standard	75mm	MN25	-	1/50	

Mandrels

Code		Working Length	Mandrel Size (mm)	Weight	Box/Qty	Each
TLMN25	94mm	47mm	16-29 (Max)	-	1/10	
TLMN152	117mm	47mm	32-152 (Max)	-	1/10	

Hole Saws

1.0.0 04.10							
	Code	Overall Length	Working Length	Mandrel Size (mm)	Weight	Box/Qty	Each
	TLHS20	53mm	20mm	MN25	-	1/10	
	TLHS25	48mm	25mm	MN25	-	1/10	
	TLHS32	48mm	32mm	MN152	-	1/5	
	TLHS38	43mm	38mm	MN152	-	1/5	
	TLHS40	45mm	40mm	MN152	-	1/5	
	TLHS50	42mm	50mm	MN152	-	1/5	
	TLHS64	43mm	64mm	MN152	-	1/5	
	TLHS70	44mm	70mm	MN152	-	1/4	
	TLHS73	44mm	73mm	MN152	-	1/4	
	TLHS75	44mm	75mm	MN152	-	1/4	
	TLHS83	44mm	83mm	MN152	-	1/4	
	TLHS86	44mm	86mm	MN152	-	1/4	
	TLHS95	44mm	95mm	MN152	-	1/4	
	TLHS102	44mm	102mm	MN152	-	1/3	

Hole Saw Kits

- Bi-metal construction Variable pitch 4/6 per inch
- Long life fast and smooth cut with shock resistant teeth
- Cuts hole in wood, plastic, machinable metal, pipe & stainless steel
- Cutting Depth up to 40mm
- TLHSEK Electrician Hole Saw Kit 9pcs 20/25/32/51/64mm
- TLHSPK- Plumbers Hole Saw Kit 9pcs 16/22/29/35/44/51mm20/25/32/51/64mm
- TLHSMK Maintenance Kit 15pcs 19/22/25/32/38/44/51/57/64mm

Pilot Drills

Code	Туре	Kit Length	Kit Width	Weight	Box/Qty	Each
TLHSEK	Electrician	225mm	145mm	1.12Kg	1/5	







Drill Bits - Masonry

- Tungsten carbide tipped
- Hardened body/shank

- brick, masonry, ceramic and slate



Overall				
Length	Hole dia.	Drill Type	Box/Qty	Each
150mm	5mm	Masonry	1/10	
150mm	5.5mm	Masonry	1/10	
150mm	6mm	Masonry	1/10	
150mm	7mm	Masonry	1/10	
150mm	8mm	Masonry	1/10	
	Length 150mm 150mm 150mm 150mm	Length Hole dia. 150mm 5mm 150mm 5.5mm 150mm 6mm 150mm 7mm	Length Hole dia. Drill Type 150mm 5mm Masonry 150mm 5.5mm Masonry 150mm 6mm Masonry 150mm 7mm Masonry	Length Hole dia. Drill Type Box/Qty 150mm 5mm Masonry 1/10 150mm 5.5mm Masonry 1/10 150mm 6mm Masonry 1/10 150mm 7mm Masonry 1/10

0.1	Overall		D.W.T.	D (O)	
Code	Length	Hole dia.	Drill Type	Box/Qty	Each
TLSDS54	100mm	5mm	SDS	1/10	
TLSDS554	100mm	5.5mm	SDS	1/10	
TLSDS5	160mm	5mm	SDS	1/10	
TLSDS5.5	160mm	5.5mm	SDS	1/10	
TLSDS6	160mm	6mm	SDS	1/10	

SDS Drill Bits - Heavy Duty

- Tungsten carbide cutting tips for quick smooth cut
- 4 cutting edges for hard masonry materials
- Double fluted shank for efficient waste removal Long life

 $(\epsilon$



Drill Bits & Sets

Step Drill Bits - Masonry

- Titanium coated
- Use for drilling metal up to 4mm thick
- Use for precision drilling steel, brass, copper aluminium, wood and plastic
- Automatically de-burs drilled holes

Code	Overall Length	Hole dia.	Drill Type	Box/Qty	Each
TLHSD4	75mm	4mm	HSS	1/10	
TLHSD5	85mm	5mm	HSS	1/10	
TLHSD55	90mm	5.5mm	HSS	1/10	
TLHSD6	105mm	6mm	HSS	1/10	

Code	Shank	Hole dia.	Pitch	Box/Qty	Each
TLSD20	22mm	4-20mm	5mm	1	
TLSD30	22mm	4-30mm	5mm	1	

HSS Drill Bits

- Ultra-hard and long lasting titanium coated high speed steel
- Suitable for most metals, plastic and wood



PRGFIX ESSENTIALS



DRILLING TOOLS

Mandrel / Hole Saws & Pilot Drills



Flat Bits - Hex Shank (Standard)

- High quality carbon steel with angled cutting head and precision round locating point
- Provides fast accurate drilling in to hard wood, soft woods and man made timber products
- Suitable for most power drills and hand braces



Auger Bits - Hex Shank

- Suitable for all wood drilling
- Precision ground, hardened high carbon steel hex shank auger bits
- Fine pitch spiral pulls auger in to the work-piece and single spur slices timber ahead of cutting edge, producing accurate holes



Pro-Safe safety first



IMPORTANT WARNING: Always wear safety protection when using any hand tools!

LOWEST PRICE



Standard Flat Bits - Hex Shank

					L	OWEST PRICE
Code	Overall Length	Hole Dia.	Drill Type	Box/Qty	Each	25+
TLFBS16	150mm	16mm	Flat Bit	1/25		
TLFBS20	150mm	20mm	Flat Bit	1/25		
TLFBS25	150mm	25mm	Flat Bit	1/25		
TLFBS32	150mm	32mm	Flat Bit	1/25		
TLFBSER	300mm	-	Extension Rod	1/10		
TLFBSET3	150mm	8-32mm	10 Piece Set	1/10		



Auger Bits - Hex Shank

	Overall				_	
Code	Length	Hole Dia.	Drill Type	Box/Qty	Each	20+
TLAB20150	150mm	20mm	Auger Bit	1		
TLAB20200	200mm	20mm	Auger Bit	1		
TLAB25200	200mm	25mm	Auger Bit	1		
TLABSET7	240mm	10-32mm	Auger Set 7 pcs	1/10		

WHEN WILL MY DELIVERY ARRIVE?

We endeavour to send all orders received before 3.00pm for next day delivery. So deliveries generally arrive between 08.30am - 17.30pm next day.

If you need help on your delivery please give us a call

PRGFIX

ESSENTIALS

CLIPS & FASTENERS

Cable Clips

- Material Impact resistant high density polyethylene (HMA014) can stand extreme hot & cold
- HDP Has high stiffness and excellent dimensional stability
- Nail Galvanised high carbon steel
- Advantages Safety nail bends before breaking, long tail for better stability and easy grip
- Suitability Wood, Masonry.
 Plasterboard & Concrete





Self Adhesive Fixing Clips to BS5750

- 0.5mm enamelled coated electrogalvanised mild steel
- 0.8mm foam cushion cello-tape adhesive acrylic for maximum effect

LOWEST PRICE

Can be used on steel and plastic

Twin & Earth Cable Clips - Flat (UV Stabilised 40°- 80°C)

Code	Clip Size	Cable Dia.	Clip Type / Colour	Box/Qty	Each	30+
CF1G	5x8mm	1mm	T&E - Grey	10/100		
CF1.5G	5x9mm	1.5mm	T&E - Grey	10/100		
CF2.5G	6x10mm	2.5mm	T&E - Grey	10/30		
CF4G	6x13mm	4mm	T&E - Grey	10/30		
CF6G	7x14mm	6mm	T&E - Grey	10/30		
CF10G	9x18mm	10mm	T&E - Grey	10/20		

Bell Cable Clips

Code	Clip Size	Nail Size	Box/Qty	Each
CB8W	2x4mm	15x1.5mm	10/100	

Round Clips

					_
Code	Cable Dia.	Clip Type / Colour	Box/Qty	Each	30+
CR4W	4mm	Round - White	10/100		
CR5W	5mm	Round - White	10/100		
CR6W	6mm	Round - White	10/100		
CR7W*	7mm	Round - White	10/100		
CR8W	8mm	Round - White	10/100		
CR9W	9mm	Round - White	10/100		
CR10W	10mm	Round - White	10/50		

* Add W = White B = Brown BLK = Black R = Red when ordering (Minimum order quantity 10 boxes)

Contact & General Aerosol Collection

Aerosol Contact Cleaner

- CC420 Contact cleaner mega wash for switches & switch gear - Heavy Duty General Aerosols
- TLAD Air-Duster Aerosol Spray for removing dust and particles from hard to reach places
- TLZGS Zinc Galvanised Aerosol Spray for corrosion protection of exposed metal surfaces



 $(\epsilon$

Code	Capacity	Weight	Box/Qty	Each
CC420	400ml	379g	1/12	
TLAD	400ml	379g	1/12	
TLZGS	400ml	379g	1/12	

Minimum order quantity: 1

We have a team of friendly, experienced and dedicated personnel ready to provide you with a high quality service.

We continue to trade solely through the electrica wholesale trade, and we would like to remind our customers should you require any help or assistance, our dedicated sales staff will be glad to help



We now have Price List 20 available in Exce format for customers who require it to update databases etc. Please contact us for your copy.



ESSENTIALS





IMPORTANT WARNING: Always wear safety protection when using any hand tools!

CLEATS & SHROUDS

Cable Cleats / Shrouds & Girder Clips

Cable Cleats

Code	Cable Dia.	No.	Cleat Type / Colour	Box/Qty	per 100
CC3	7.6mm	3	Cable - Black	16	
CC4	10.0mm	4	Cable - Black	50	
CC5	12.7mm	5	Cable - Black	50	
CC6	15.2mm	6	Cable - Black	50	
CC7	17.8mm	7	Cable - Black	50	
CC8	20.3mm	8	Cable - Black	50	
CC9	22.8mm	9	Cable - Black	50	
CC10	25.4mm	10	Cable - Black	50	
CC11	27.7mm	11	Cable - Black	20	
CC12	30.4mm	12	Cable - Black	20	
CC13	35.0mm	13	Cable - Black	20	
CC14	35.6mm	14	Cable - Black	20	
CC16	40.6mm	16	Cable - Black	20	
CC18	45.7mm	18	Cable - Black	20	
CC20	50.8mm	20	Cable - Black	20	

Selection Guide

Odioction duido								
Cable				No. 0	Cores			
Size	1	2	3	4	7	12	19	
1.5mm		CC5	CC6	CC6	CC7	CC8	CC10	(
2.5 mm		CC6	CC6	CC6	CC7	CC9	CC11	(
4.0mm		CC6	CC7	CC7	CC8	CC11		
6.0mm		CC7	CC7	CC8				
10.0mm		CC8	CC8	CC8				
16mm		CC8	CC9	CC10				
25mm		CC10	CC11	CC12				
35mm		CC12	CC12	CC14				
50mm	CC7	CC11	CC12	CC14				
70mm	CC8	CC12	CC14	CC16				
95mm	CC9	CC14	CC16	CC18				
120mm	CC10	CC16	CC16	CC20				
150mm	CC11	CC16	CC18	TC9				
185mm	CC12	CC18	CC20	TC9				
240mm	CC14	CC20	TC9	TC10				
300mm	CC16	TC9	TC10	TC11				
400mm	CC16	TC10	TC11	TC14				
500mm	CC18					_		

630mm CC20 800mm TC9 1000mm



- Available in PVC or Low Smoke and Fume LSF)
- Size 20mm and 25mm
- Colour Red, White, Black and Orange

		•	
Dia.	Type/Colour	BoxQty 10	10+
20mm	Shroud - Various	M0Q: 1	

* Add WHI = White BRO = Brown BLK = Black RED = Red when ordering (Minimum order quantity 10).

- Made from low density polyethylene providing high strength and impact resistance
- Temperature -35C° to 105C°
- UV-light resistant / corrosion resistance
- Suitable for indoor and outdoor use



- Girder Clips are suitable for fixing cable, conduit and electrical fixtures & fittings.
- They are generally used in situations where the fixings are difficult and prove useful in saving labour time and money.

Girder Clips

CE

- BXS (small), BXM (medium), BXL (large) series of cable clips have electrogalvanised zinc coating with 8-15 micron of zinc to DIN-50021
- 90 Hour of salt water spray medium resistance
- BE24, BE58 horizontal beam clips mechanical zinc coating up to 20 micron 500 Hours of salt water spray heavy duty resistance - 90Kgm load
- BF1 vertical beam 20 microns mechanical zinc coating 70 Kgm static load
- BG812 series 20 microns zinc coating 11Kgm static weight

		Clip	Clip		
Code	Cable Dia.	Thickness	Type / Colour	Box/Qty	100 +
Small					
BXS89	6-7mm	2.4mm	Cable - Zinc	100	
BXS1011	10-11mm	2.4mm	Cable - Zinc	100	
BXS1214	-	2.4mm	Cable - Zinc	100	
BXS2024	20-24mm	2.4mm	Cable - Zinc	100	
Medium					
BXM89	7-9mm	4.7mm	Cable - Zinc	100	
BXM1011	10-11mm	4.7mm	Cable - Zinc	100	
BXM1214	12-14mm	4.7mm	Cable - Zinc	100	
BXM1519	15-19mm	4.7mm	Cable - Zinc	100	
BXM2024	20-24mm	4.7mm	Cable - Zinc	100	
Large					
BXL89	7-9mm	8-12mm	Cable - Zinc	100	
BXL1011	10-11mm	8-12mm	Cable - Zinc	100	
BXL1214	12-14mm	8-12mm	Cable - Zinc	100	
BXL1519	15-19mm	8-12mm	Cable - Zinc	100	
BXL2024	20-24mm	8-12mm	Cable - Zinc	100	

PRŒIX

ESSENTIALS

- · Girder Clips are suitable for fixing cable, conduit and electrical fixtures & fittings.
- . They are generally used in situations where the fixings are difficult and prove useful in saving labour time and money.





EATON CABLE CLIPS METAL

Beams Clamps & Jack Chain

Horizontal Beam/Flange Clips

Zinc coated



. (
Code	Box/Qty	per 100
BE24	25	
BE58	25	

Code: BF1 Vertical Beam Flange Clips

- 1.5-4mm Vertical Hanging Clip 7mm Hole
- 7inc coated

((



BoxQty 25	per 100
M00: 1	

Code: BMA416

Tee Bar False Ceiling Clips

 25mm Tee Bar Clip M6 x Thread - 16mm Long - 22Kgms

Zinc coated

 $(\epsilon$



per 100

Horizontal Beam Conduit Clips Zinc coated



((

Code	Clip Size	Cable Size	Box/Uty	per 100
BG812E24	3-8mm	18-27mm	25	
BG812E58	8-14mm	18-27mm	25	

Code: BC10 Beam Clamps

- Beam Clamp 19mm Beam / 11mm Stud / 240Kg Load
- Zinc coated

(6

Length	Width	Depth
Long	n/a	n/a



BoxQty 1/100	per 100
M00: 1	


Code: JC10G

Jack Chain (Max Load 7.5Kgms)

- Single link, jack chain 3mm thickness
- Made out of pre-galvanised material Colour - Electroplate Galvanised Steel or Black Max working load - 7.5kgms Available - 10Mtr Lengths



Length	Width
160mm	100mm



BoxQty 1/15	Each	15+
M00: 1		

PRŒFI

FSSENTIALS



FIXING & FASTENERS

Catenary Wire & Accessories

General Features

- High Tensile Steel Wire:- Thickness: 3mm Finish:- Pre Galvanised Preformed Wire
- Available in Lengths 30, 50 and 100Mtrs Max Load: 155Kg
- Accessories:- BZP Finish
- Ring on plate size (50x50Mtrs) Galv 6x110mm, BZP Finish (CWWRP) used for mounting for small boats, securing equipment
- Catenary's Wire Tension (CWT)
- Centenary Wire Grip (CWWG) Diameter 1/8 Inches, Galvanised 3mm Diameter Grip the return end of wire when in a loop
- CWEYE (Wire Edge) Thimble forms the rope loop to prevent wear and tear. Length 25mm, Dia. 3mm, BZP Finish

Catenary Wires

	Length	Wire dia.	Wire		
Code	Mtrs	(mm)	Type/Colour	Box/Qty	Each
CW30	30	3	Wire - Zinc	1	
CW50	50	3	Wire - Zinc	1	
CW100	100	3	Wire - Zinc	1	
CW30KIT	-	-	Kit	1	

Accessories

	Size	Accessory		
Code	(mm)	Type/Colour	per Box	Each
CWEYE	3	Eye	20	
CWWG	3	Grip	20	
CWT	6x110 (Body)	Tensioner	1	
CWWRP	50x50	Wall Ring Plate	1	
CWSTRAP	152	Leather Strap	1	
CWWHP	50x50	Wall Hook Plate	1	

CW30KIT - Kit consists of:-1 x CWWHP. 1 x CWWRP. 1 x CWT.

Available in 30,50 and 100 metres

 Catenary Wires · High tensile steel

 Wire 3mm thick Max. Load 155Kg

 Pre-galvanised Accessories BZP finish

1 x 30Mtr Caternary Wire, 2 x CWEYE, 4 x CWWG

All Round Band Fastenings

- All purpose flexible yet strong fixing hand
- Neat versatile & efficient
- Easy to cut and bend to any shape Pre-punched holes to enable fixing
- with bolts, screws or nails
- Resistant to chemical and marine corrosion
- Application Securing, Supporting, Strapping of cable, Guttering, Fencing, Lighting, Trunking,

Code: CV

Suspension 'V' Clip - Chrome Plated

- Bright zinc finish steel
- Fits easily into 20mm hole



Dimensio			
Length	Width	Weight	
35	40	7g	

BoxQty 10/100	per 100
M00: 1	

PVC Coated & Galvanised (Max Load 85Kgms)

	Dimensions	Band Size	Band		
Code	LxWxH (mm)	(mm)	Type/Colour	Box/Qty	Each
ARB12BLK	12 x 10 Mtrs	12	Pack (Black)	1/10	
ARB12WHI	12 x 10 Mtrs	12	Pack (White)	1/10	
ARB12RED	12 x 10 Mtrs	12	Pack (Red)	1/10	
ARB12GALV	12 x 10 Mtrs	12	Pack (Galv)	1/10	

Mounting Box Bracket

- Completely adjustable fits a range of stud spacing and 38mm or 54mm deep boxes
- Pre-punched screw holes provide for easy installation
- Bar is marked with scale for stud spacing
- Finish Pre-Galvanised

	Dimensions (mm)		All A	L	JWEST PRI	υE
Code	Stud Spacing	Weight	Box/Qty	Each	50+	
BMB16	11 inch - 18 inch	197g	1/50			
BMB26	15 inch - 26 inch	270g	1/50			

PROFIX

ESSENTIALS

Jointing Kits for SWA Cable - to BS6910

- Designed to BS6910
- Suitable for 600/1000V PVC, XLPE armoured or un-armoured cable
- Size 1.5 to 300mm² (cable splices are not included in the kit)
- Supplied with instructions
- Mechanical connector up to 35mm size

		Dimensions			-
Code	Туре	Cable Size (mm)	Weight	Box/Qty	Each
CJK0*	Straight	1.5-6	57.5g	1	
CJK1*	Straight	10-16	1100g	1	
CJK2*	Straight	16-35	2400g	1	
CJK3	Straight	35-75	5800g	1	
CJK4	Straight	95-120	6800g	1	
CJK5	Straight	150-185	13330g	1	
CJK6	Straight	240-300	18880g	1	

^{*}Please refer to the Jointing Kit selection chart at the back of the catalogue for each size of cable.



Jointing Kits, Moulded Enclosures & Connection Boxes

Code: JBO

Moulded Enclosure - IP55

- Junction box
- positions
- Includes 5 x 2.5mm connectors



Dir	nensions (m	ım)			
Length	Width	Width	Weight	BoxQty 10/60	Each
75	75	37	48g	M00: 10	



CJK0/CJK1/CJK2 Complete with Mechanical Connector

	ments suc and cable	ch as suspo ducts	ended		
Dimensions (mm)					
Length	Width	Width	Weight		

Moulded Enclosure - IP55

 10 entries, 2 floor entries, suitable for confined installation



JBO Mini c/w Connector Strip 3x2.5mm²

BoxQty 1/40	Each
M00: 1	

Code: CHOCBOX

Lighting Connection Box Mains Voltage - IP44

- Lighting Chocbox with clamp and screws
- A plastic box to insulate connector blocks
- Used as a junction box for fixed wiring
- Used as an in-line connector



Dim	nensions (n	nm)				
Length	Width	Depth	Weight	BoxQty 1/100/200	Each	200+
90	50	24	29g	M00: 1		

Code: LCBOX

Code: JBOMINI

Junction box

Lighting Connection Box Low Volta

- Moulded from HDPE making it long lasting and durable
- Available with 3 pole strip connector rated at 15Amps
- Removable snap on cover giving uninterrupted access to connectors

mensions (m	ım)		
Width	Depth	Weight	
45	24	33g	
	Width		Width Depth Weight

age	1	W.	2	
K	*	1		
				5
(
		100		

BoxQty 1/100	Each
M00: 1	

WHAT ARE YOUR DELIVERY CHARGES?



CT368



CABLE MANAGEMENT

Weatherproof Connectors, Connector Blocks & Strips

3 Pole Weatherproof Connectors

- IP68 fully dust and waterproof.
- Supplied with rubber glands
- High quality material
- Nickel plated copper contacts
- Screw terminals

Junction Box supplied with quick connector terminals





Code	Description	Colour	Dimensions (mm)	Ingress	Termination	Cable Wiring	Box/Qty	Each
CBX368	3 Pole Box Connector IP68 16A	Transparent	128.5 x 72 x 35.5	IP68	3 pole terminal block	5mm Min; 14mm max.	1	
CST368	3 Pole Connector Straight IP68 16A (5-14mm) Cable	Black	116.5 x Ø32.5	IP68	Screw fixing	5mm Min; 14mm Max.	1	
CT368	3 Pole Connector Tee IP68 16A (5-14mm) Cable	Black	116.5 x 90 x 27	IP68	Screw fixing	5mm Min; 14mm Max.	1	

CST368

Code: WPC

Waterproof Connection Unit (Male & Female) IP68

Waterproof connector 10Amps IP68 (Max. 240V)

IP68 waterproof plug and socket to suit

CBX368

cable 5-9mm

 Residual current circuit breaker (RCD) must be fitted to the supply

			ð
Dimensio	ons (mm)	-	۳
Length	Width	Weight	
127	27	60a	

BoxQty 1 M00: 1

In Line Connector 3 Core Cable - IP68

- IP68 waterproof cable connectors
- Connector Type: Triple Pole (3 Core)
- Electrical Rating: 32A 450V
- Terminal Capacity: 1x4mm2 per hole (incoming/outgoing sides)

Gland Size:

ICL368:- M25 x 1.5 / cable size 7-13.5mm

Dim			
Code	Length	Width	Weight
ILC368	80	30	44g

BoxQty 1	Each
M00: 1	

Porcelain Connector Blocks

- Inserts are nickel plated brass
- Screws are galvanised
- Standard CE(BS EN60998)
- Porcelain housing which is hard and solid. has high melting point, inflammable and is

resistant to chemicals 2 and 3 pole complete with central hole fixing									
	Dimensions (mm2)	Block	Block						
Code	Cross Section	Amps	Way	Box/Qty	Each				
PCB52	4	5	2 Way	60					
PCB53	4	5	3 Way	30					
PCR152	10	15	2 M/av	20					

	Difficitional (ITITIZ)	DIOCK	DIOCK		
Code	Cross Section	Amps	Way	Box/Qty	Each
PCB52	4	5	2 Way	60	
PCB53	4	5	3 Way	30	
PCB152	10	15	2 Way	20	
PCB153	10	15	3 Way	20	
PCB302	16	30	2 Way	15	
PCB51	4	5	1 Way	120	
PCB151	10	15	1 Way	60	
PCB301	16	30	1 Way	30	

Connector Strips - Flexible

- Polyethylene works up to 80°C
- Available in 3A.5A.15A.30A and 60A
- Brass inserts



Polyethylene upto 80°C

					ın	WEST PRI
	Dimensions (mm²)	Block	Block		LO	WESTTIII
Code	Cross Section	Amps	Type/Way	Box/Qty	Each	100+
CS3	4	3	H+12W	1000		
CS5	6	5	H+12W	500		
CS15	12	15	H+12W	200		
CS30	16	30	H+12W	200		
CS60	25	60	H+12W	100		

PROFIX

ESSENTIALS

PVC Electrical Tapes - Flame Retardant

- Thickness: 0.13mm
- · Self-extinguishing before 50mm length
- Adhesion to steel
- Insulation resistance

Availab	le in 30Mtr	s & 20M1	irs		RDANT ION TAPE	10	
	Dimension	ns (mm)			AL TAP	E 10	١
Code	Length	Width	Туре	Weight	Box/Qty	Each	
TP1920	20 (Mtrs)	19	PVC	64g	10/100		Ī
TP1933	33 (Mtrs)	19	PVC	110g	10/200		Ī
		4 11 E B 1	NAME OF TAXABLE PARTY.	A SHEET	3		



Electrical Tapes, Warning Tape and Signs

Note:- Please Add Suffix for Colours required when ordering.

BLK = Black WHI = White. GY = Green/Yellow YEL = Yellow VIO = Violet

GRN= Green

BLU = Blue BRO = Brown ORA = Orange GRY=Grev

*Packed 10 rolls per sleeve

All Purpose Gaffer Tape

- 48mm Wide 50Mtrs long
- Heavy duty cloth back adhesive tape
- Suitable where normal PVC tape would lose adhesion due to ingress of water
- Used for fixing cable to wall/floor for general repairs

	Dimensio	ons (mm)			
Code	Length	Width	Weight	Box/Qty	Each
TPG5050BLK	50Mtr	48	582g	1/24	
TPG5050SIL	50Mtr	48	582g	1/24	

MENT BUTY DOCT THE

Warning Sign Labels (Self Adhesive)

	Dimensions			
Code	LxW (mm)	Label Legend	Box/Qty	per Pack
WL415V	50 x 50	415v	1	
WL240V	50 x 50	240v	1	
WL400V	50 x 50	400v	1	
WL230V	50 x 50	230v	1	
WLDHV	50 x 50	High Voltage	1	
WLDIE	50 x 50	Danger Isolate Elsewhere	1	
WLDOD	50 x 50	Danger of Death	1	
WLEF	50 x 50	Electric Flash	1	
WLRES	50 x 50	Risk of Electric Shock	1	

Self Amalgamating Tape Black

- Chemically bonds to itself and to irregular surfaces and shapes
- Possesses excellent resistance to outdoor exposure, voltage and water
- Suitable for splicing and repair of power distribution cables, pipes and hoses
- Provides watertight seals and protection against corrosion

	Dimensions (mm)				
Code	Length	Width	Weight	Box/Qty	Each
TPSA1910BLK	10Mtr	19	100g	1	

Warning Tape for Laying Electrical Cable

- 150mm wide x 50 microns thickness
- Provides a strong warning to prevent imminent danger from electrical cables beneath
- Marking "Caution electrical cable below

	Dimensio	ons (mm)	-		
Code	Length	Width	Weight	Box/Qty	Each
WT	365Mtr	150	2.2Ka	1/4	







CABLE MANAGEMENT

Cable Lugs & Splices

Lugs

- Tinned copper heavy duty
- Non-insulated lugs
- Stud size 5mm² 20mm²
- Conductor size 1.5mm² 600mm
- All terminals are provided with an inspection hole to ensure the conductor is fully inserted before crimping
- The internal barrel diameter suit standard cables as defined in BS 6360



- Copper terminal non-insulated conductor size 1.5mm² - 600mm²
- Splices available in sizes 6mm² 400mm² (straight connector)



Cable Lugs

		Lug Dimensi	ons (mm)			
Code	Size	Length	Stud Size	Lug Type	Box/Qty	per 100
CL1.5	1.5	16	5	3.7	100	
CL2.5	2.5	20	5,6	9	100	
CL4	4	20	5,6	4.8	100	
CL6	6	23(5.6) 27(8)	5,6,8	5.5	100	
CL10	10	25,27,32	5,6,8,10,12	6.2	100	
CL16	16	30,30,37,38	6,8,10,12	7.1(6.8)7.8(11.12)	100	
CL25	25	30,30,37,37	6,8,10,12	8.8	100	
CL35	35	35,38,43	8,10,12	10.6	100	
CL50	50	43	8,10,12	12.4	100	
CL70	70	50	8,10,12,16	14.7	50	
CL95	95	55,55,55,61	8,10,12,14,16	17.4	25	
CL120	120	64	8,10,12,14,16,18,20	17.4	50	
CL150	150	69	8,10,12,14,16	21.5	50	
CL185	185	78	8,10,12,16	23.5	40	
CL240	240	92	10,12,14,16,20	26.5	25	
CL300	300	101	12,14,16,20	30	20	
CL400	400	114	16,20	36.5	10	
CL500	500	124	16,20	39	5	

*Please add stud size to the code with forward slash (/) e.g. CL10/6.

Cable In Line Connectors - (Copper)

	(Connector (Dimensions (r	nm)	Connector		
Code	Size	Length	Inner Dia.	Outer Dia.	Туре	Box/Qty	per 100
SP6	6	15	3.8	5.5	Straight/Splice	100	
SP10	10	20	4.5	6.2	Straight/Splice	100	
SP16	16	20	5.4	7.1	Straight/Splice	100	
SP25	25	32	6.8	8.8	Straight/Splice	100	
SP35	35	36	8.2	10.6	Straight/Splice	100	
SP50	50	40	9.5	12.4	Straight/Splice	100	
SP70	70	45	11.2	14.7	Straight/Splice	50	
SP95	95	45	13.5	17.4	Straight/Splice	25	
SP120	120	45	15	19.4	Straight/Splice	50	
SP150	150	55	16.5	21.5	Straight/Splice	50	
SP185	185	60	18.5	23.5	Straight/Splice	40	
SP240	240	80	21	26.5	Straight/Splice	25	
SP300	300	85	23.5	30	Straight/Splice	20	
SP400	400	85	28.5	36.5	Straight/Splice	10	

Butt Splice

- Tinned copper tube splices
- Designed for joining low voltage conductor from 6mm² -400mm²
- They feature an internal taper at both ends to ease the insertion of the conductor and a central stop to ensure correct position

PROFIX

ESSENTIALS

- Manufactured by UL approved ISO9002 factory
- Female, Male and Splices as per UL310 standard
- Material: Copper
- Rings and Forks as per UL 486A

Pre-Insulated Copper Terminal Lug Rings

А	Ring Dimensions (mm)			Ring			
Code	Ring	Stud	Inner Dia.	Washer	Type/Colour	Box/Qty	per 100
PLR1537R	0.5-1.5	3.7	4.3	10	Ring/Red	100	
PLR1543R	0.5-1.5	4.3	4.3	10	Ring/Red	100	
PLR1564R	0.5-1.5	6.4	4.3	10	Ring/Red	100	
PLR2543B	1-2.5	4.3	4.9	10	Ring/Blue	100	
PLR2553B	1-2.5	5.3	4.9	10	Ring/Blue	100	
PLR2564B	1-2.5	6.4	4.9	10	Ring/Blue	100	
PLR643Y	2.5-6	4.3	6.7	14	Ring/Yellow	100	
PLR653Y	2.5-6	5.3	6.7	14	Ring/Yellow	100	
PLR664Y	2.5-6	6.4	6.7	14	Ring/Yellow	100	

Male Push-On Terminal

В	Terminal Dimensions (mm)		Terminal				
Code	Size	Tab	Height	Size WxL	Type/Colour	Box/Qty	per 100
PLM15R	0.5-1.5	.250	.08	6.3 x 21	Male/Red	1/10	
PLM25B	1-2.5	.250	.08	6.3 x 21	Male/Blue	1/10	
PLM6Y	2.5-6	.250	.08	6.3 x 25	Male/Yellow	1/10	

Female Push-On Terminal

С	Terminal Dimensions (mm)			Terminal			
Code	Size	Tab	Height	Size WxL	Type/Colour	Box/Qty	per 100
PLF15R	0.5-1.5	.250	.08	7.4 x 20.8	Female/Red	100	
PLF25B	1-2.5	.250	.08	7.4 x 20.8	Female/Blue	100	
PLF6Y	2.5-6	.250	.08	7.4 x 24.8	Female/Yellow	100	

Splices Butt Connection

D	Splice Dimensions (mm)			Splice			
	Outer						
Code	Size	Dia.	Inner Dia.	Length	Type/Colour	Box/Qty	per 100
PLS15R	0.5-1.5	4.3	1.7	2.6	Splice/Red	100	
PLS25B	1-2.5	4.3	2.3	2.6	Splice/Blue	100	
PLS6Y	2.5-6	6.5	3.4	2.7	Splice/Yellow	100	
Forks							

Torico						
Fork Dimensions (mm)			m)	Fork		
Fork	Stud	Insulator	Length	Type/Colour	Box/Qty	per 100
0.5-1.5	3.7	10	21.2	Fork/Red	100	
0.5-1.5	4.3	10	21.2	Fork/Red	100	
0.5-1.5	6.4	10	21.2	Fork/Red	100	
1-2.5	4.3	10	21.2	Fork/Blue	100	
1-2.5	5.3	10	21.2	Fork/Blue	100	
1-2.5	6.40	10	21.2	Fork/Blue	100	
2.5-6	4.3	10	25.5	Fork/Yellow	100	
2.5-6	5.3	10	25.5	Fork/Yellow	100	
2.5-6	6.4	10	25.5	Fork/Yellow	100	
	Fork 0.5-1.5 0.5-1.5 0.5-1.5 1-2.5 1-2.5 1-2.5 2.5-6 2.5-6	Fork Stud 0.5-1.5 3.7 0.5-1.5 4.3 0.5-1.5 6.4 1-2.5 4.3 1-2.5 5.3 1-2.5 6.40 2.5-6 4.3 2.5-6 5.3	Fork Stud Insulator 0.5-1.5 3.7 10 0.5-1.5 4.3 10 0.5-1.5 6.4 10 1-2.5 4.3 10 1-2.5 5.3 10 1-2.5 6.40 10 2.5-6 4.3 10 2.5-6 5.3 10	Fork Stud Insulator Length 0.5-1.5 3.7 10 21.2 0.5-1.5 4.3 10 21.2 0.5-1.5 6.4 10 21.2 1-2.5 4.3 10 21.2 1-2.5 5.3 10 21.2 1-2.5 6.40 10 21.2 2.5-6 4.3 10 25.5 2.5-6 5.3 10 25.5	Fork Stud Insulator Length Type/Colour 0.5-1.5 3.7 10 21.2 Fork/Red 0.5-1.5 4.3 10 21.2 Fork/Red 0.5-1.5 6.4 10 21.2 Fork/Red 1-2.5 4.3 10 21.2 Fork/Blue 1-2.5 5.3 10 21.2 Fork/Blue 1-2.5 6.40 10 21.2 Fork/Blue 2.5-6 4.3 10 25.5 Fork/Yellow 2.5-6 5.3 10 25.5 Fork/Yellow	Fork Stud Insulator Length Type/Colour Box/Oty 0.5-1.5 3.7 10 21.2 Fork/Red 100 0.5-1.5 4.3 10 21.2 Fork/Red 100 0.5-1.5 6.4 10 21.2 Fork/Red 100 1-2.5 4.3 10 21.2 Fork/Blue 100 1-2.5 5.3 10 21.2 Fork/Blue 100 1-2.5 6.40 10 21.2 Fork/Blue 100 2.5-6 4.3 10 25.5 Fork/Yellow 100 2.5-6 5.3 10 25.5 Fork/Yellow 100

CABLE MANAGEMENT

Insulated Lugs, Rings and Terminals

CED ELECT

Pin Connector

E	Pin Dim	ensions (mm)	Pin		
Code	Length	Cable	Type/Colour	Box/Qty	per 100
PLP12B	12	1-2.5 ²	Pin/Red	100	
PLP12R	12	0.5-1.5 ²	Pin/Blue	100	
PLP14Y	14	2.5-6 ²	Pin/Yellow	100	

Female Bullet Connector Pre-Insulated

F	Bullet Dimensions (mm)		Bullet		
Code	Tab Cable		Type/Colour	Box/Qty	per 100
PLFB15R	4 0.5-1.52		Bullet/Red	100	
PLFB25B	4	1-2.52	Bullet/Blue	100	
PLFB6Y	5	2.5-62	Bullet/Yellow	100	

Male Bullet Connector Pre-Insulated

G	Bullet Dimensions (mm)		Bullet		
Code	Tab Cable		Type/Colour	Box/Qty	per 100
PLMB15R	4 1.52		Bullet/Red	100	
PLMB25B	4	2.52	Bullet/Blue	100	
PLMB6Y	5	62	Bullet/Yellow	100	





ESSENTIALS



CABLE MANAGEMENT

Pyro Cable Clips & Nylon Glands

- Clips RCHJ MICC / FP200 / FIRTUF & PYRO
- Saddles MICC / FP200 / FIRTUF Cable & Pyro
- Clips and Saddles copper covered with PVC
- Available in Red, and White colours

Clips - RCHJ MICC/FP200/FIRTUF & PYRO

Code	Size (mm²)	Clip Type		Box/Qty	per 100
AP7	2L 1.5mm	RCHJ32/RCHL28	Plastic Coated	100	
AP8	2L 2.5mm/3L 1.5	RCHJ34/RCHL32	Plastic Coated	100	
AP9	3L 2.5mm/4L 1.5	RCHJ37/RCHL34	Plastic Coated	100	
AP10	4L 2.5mm	RCHJ40/RCHL37	Plastic Coated	100	
AP11	4H 2.5mm	RCHJ43/RCHL40	Plastic Coated	100	
AP12	2H 10mm	RCHJ59/RCHL54	Plastic Coated	100	

*Add colour after the code e.g. WHI, RED

Saddle MICC/FP200/Fire TUFF Cable & Pyro

Code	Size (mm²)		Saddle Type	Box/Qty	per 100
AP7S	2L 1.5mm	RSFJ302/RSFL302	Plastic Coated	100	
AP8S	2L 2.5mm/3L 1.5	RSFJ342/RSFL342	Plastic Coated	100	
AP9S	3L 2.5mm/4L 1.5	RSFJ372/RSFL372	Plastic Coated	100	
AP10S	4L 2.5mm	RSFJ422/RSFJ422	Plastic Coated	100	
AP11S	4L 2.5mm	RCHJ43/RCHL40	Plastic Coated	100	
AP12S	2H 10mm	RCHJ59/RCHL54	Plastic Coated	100	

*Add colour after the code e.g. WHI, RED

*Add colour after the code e.g. WHI, RED N.B. For AP Cable Clip use please refer to the Clips Selection Chart at the back of the catalogue.

- Available in Red, White, Orange, bare Copper and Black colour
- Bare clips RC plastic coated saddles RSFT Bare Saddles - RS plastic coated Clips - RCHJ



*Please quote B for Black W for White & R for Red when ordering. *Grey Colour on request.

Mineral Insulated Glands, Pots & Seals RGM & RPS

	Dimensions (mm							
Code RGM	Size (mm)	Length	Code RPS	Туре	Box/Qty	RGM per 10	RPS per 10	RPSL per 10
2L1.5	20	33	2L1.5	Gland/Pot/Seal	10			
2L2.5	20	33	2L2.5	Gland/Pot/Seal	10			
3L1.5	20	33	3L1.5	Gland/Pot/Seal	10			
3L2.5	20	33	3L2.5	Gland/Pot/Seal	10			
4L1.5	20	33	4L1.5	Gland/Pot/Seal	10			
4L2.5	20	33	4L2.5	Gland/Pot/Seal	10			

Nylon Glands

Code	12.5mm Thread Polyamide Neoprene Rubber	Rating	Pack/Qty	per 100
NG2068B/W/R	20mm Standard for Dia. 6-12mm	IP68	100/1000	
NG2568B/W/R	25mm Standard for Dia. 13-18mm	IP68	100/1000	
NGL2068B/W/R	Locknuts for 20mm (Small & Standard Glands)	IP68	100/1000	
NGL2568B/W/R	Locknuts for IP68 25mm Glands	IP68	100/1000	

Nylon Glands Locknuts Kits

	(Includes 10 Glands & 10 L	18			
Code		Colour	Rating	Pack/Qty	Each
NG20WKIT	20mm Kit (10 Pack)	White	IP68	10/100	
NG20BKIT	20mm Kit (10 Pack)	Black	IP68	10/100	
NG20RKIT	20mm Kit (10 Pack)	Red	IP68	10/100	

PRŒIX

ESSENTIALS

Cable Ties Colours:- Black & Natural

- Working temperature range: -40°C to +85°C
- Bent rounded tip allows easier picking, insertion and pull-out
- Resistance to oil and grease
- Material: Nylon 6/6
- Smooth rounded edges for easier handling and installation



CABLE MANAGEMENT

Cable Ties, Plugs and Straps

	Cable Ties	Dimensions			
Code	Size (mm)	Length (mm)	Tensile Strength	Box/Qty	per 100
CT100/25N/B	2.5	100	8	100/10000	
CT140/36N/B	3.6	140	13	100/40000	
CT160/48N/B	4.8	160	20	100/30000	
CT200/48N/B	4.8	200	22	100/20000	
CT300/48N/B	4.8	300	22	100/10000	
CT370/48N/B	4.8	370	22	100/5000	
CT300/76N/B	7.6	300	55	100/5000	
CT370/76N/B	7.6	300	55	100/4000	
CT530/90N/B	9	530	55	100/2000	
CT710/90N/B	9	710	77	100/1000	





Cable Ties (316) - Stainless Steel

- Stainless steel with a unique locking ball mechanism that allows the tie to be quickly and easily installed
- Ideal for use in environmentally harsh conditions where subjected to various chemicals, acids, salts, high temperatures
- Temperature: -35°C to +180°C
- Material: A4 316 stainless steel



Available in Black or Natural **CTMM**

CT4WAN/B

- They're used with cable ties up to 9mm wide
- The wall plug bases avoid friction of the cable on the wall protecting the installation



Cable Ties - Base & plug

To accept 4.8mm maximum width ties

Mounting should be applied to clean dry

smooth surfaces, free from dust, oils

	Dimensio	ons (mm)		
Code	Length	Width	Box/Qty	100+
CT360/46S	360	4.8	100	
CT520/46S	520	4.6	100	

	Dimensio	ns (mm)		
Code	Length	Width	Box/Qty	per 100
CT4WAN/B	28	28	100/10000	
CTMM	43.5	9	100/10000	





EARTHING ESSENTIALS

Earthing Rods, Clamps, Blocks, Strips and Boxes

Earth Rods Copper Bond to BS7730

- Approved to BS7430
- Copper band earth rod 0.25mm
- Offers excellent corrosion resistance
- High tensile strength
- Available in: 3/8" non-expandable accessories clamp only 5/8" rod - accessories clamps (split and standard type) driving stud and coupler



	Dimensions		Copper				
Code	Length Width		Thickness	Туре	Box/Qty	Each	50 pcs
ER384	4ft	3/8"	0.25mm	Rod	1/50		
ER584	4ft	5/8"	0.25mm	Expandable	1/20		
ERCL38	-	3/8"	0.25mm	Rod	1/25		
ERCL58	-	5/8"	0.25mm	Clamp	1/25		
ERCS38	-	3/8"	0.25mm	Clamp Split	1		
ERCS58	-	5/8"	0.25mm	Clamp Split	1		
ERDS58	-	5/8"	0.25mm	Driving Stud	1		
EREC58	-	5/8"	0.25mm	External Coupler	1		
ERPITP	-	-	-	Pit Plastic	1		
ERPIT/HD			-	Pit (Heavy Duty)	1		

Earth Clamps

- Approved BS951
- ECL14 Indoor use only (non-corrosive and dry conditions)
- ECL15 All conditions (corrosive and humid conditions)

Available in:

- 12-32mm pipe dia. 32-50mm Pipe dia.
- 50-75mm Pipe dia.

Dimensions	

	Difficilision	110				
Code	Overall Length (mm)	Fits Pipe	Clamp Type	Box/Qty	Each	500 +
ECL14	155	1/2 - 1.1/4"	Earth Clamp	10/500		
ECL15	155	1/2 - 1.1/4"	Earth Clamp	10/500		
ECL14/2	205	1.1/4 - 2"	Earth Clamp	20/400		
ECL14/3	310	2 - 3"	Earth Clamp	20/400		
ECL15/2	205	1.1/4 - 2"	Earth Clamp	20/400		
ECL15/3	310	2 - 3"	Earth Clamp	20/400		
ECL16	160	2 x 16	Earth Clamp	20/500		

Earth Strip

- Copper earth strip width 12mm
- Hole distance 5mm length 20Mtrs



Dimensions (mm)					
Code	Length	Width	Weight	Box/Qty	Each
CS	20Mtr	12	1035g	1/10	

Earth Terminal Blocks

- Brass earth blocks 4 way/8 way double pole
- Takes 16mm and 25mm conductors
- Nickel plated base slotted screws



	Dimensions (mm)						
Code	Length	Width	Depth	Weight	Box/Qty	Each	100+
EB4	51	19	11	88g	25/200		
EB8	87	19	12	148g	10/100		

Earth Electrode Box - Green

- Earth rod box
- Earth rod/cable entry 7-10.5mm
- Available in: 81x81mm / 106x106mm
- Depth: 67mm



	Dim	ensions (n	nm)			
Code	Length	Width	Depth	Weight	Box/Qty	Each
EB44GRN	106	106	67	233g	1/10	

PROFIX

ESSENTIALS

PVC Sleeving to BS2943-3

- Maximum operating temperature 85°C
- Self extinguishing to BS2848
- Voltage proof @ 3000V to BS2848
- Insulation resistance to BS2848 10 ohms/cm
- Dielectric strength 20kV/mm
- Tensile strength 15mPa
- Available in 100Mtr coils





	Dimensions		Sleeving			
Code	Length (Mtrs)	Dia. (mm)	Colour	Туре	Mtrs	100 Mtrs
S2GY	100	2	Green/Yellow	Earth Sleeving	100	
S3BLK	100	3	Black	Sleeving	100	
S3GY	100	3	Green/Yellow	Earth Sleeving	100	
S3BR0	100	3	Brown	Sleeving	100	
S3BLU	100	3	Blue	Sleeving	100	
S3RED*	100	3	Red	Sleeving	100	
S4GY	100	4	Green/Yellow	Earth Sleeving	100	
S4BR0	100	4	Brown	Sleeving	100	
S4BLU	100	4	Blue	Sleeving	100	
S4RED*	100	4	Red	Sleeving	100	
S5GY	100	5	Green/Yellow	Earth Sleeving	100	
S6GY	100	6	Green/Yellow	Earth Sleeving	100	
S10GY	100	10	Green/Yellow	Earth Sleeving	100	

*Add colour after the code e.g. BLK, BLU, BRO instead of RED

	Dim	nensions	Shrink			
Code	Length (Mtrs)	Dia. (mm)	Colour	Туре	Box/Qty	Each
HSB93B	11.5	2.4	Black (boxed)	Heat Shrink	1	
HSB125B	11.5	3.2	Black (boxed)	Heat Shrink	1	
HSB250B	7.5	6.4	Black (boxed)	Heat Shrink	1	
HSB375B	6.5	9.5	Black (boxed)	Heat Shrink	1	
TLHSK	40	2/2.5/5/7/10/13	Black (kit)	Heat Shrink Kit	1	

Grommet Edging Strips - Black

- Protects sharp or delicate edges
- Fits irregular shapes
- Fits a range of panel sizes from 1mm to 6.8mm
- Supplied in handy 50Mtr roll
- Colour: Black

	Dimensions (mm)					
Code	Length (Mtrs)	Edge	Material	Туре	Box/Qty	Each
GMS2	50	1-2	Rubber	Strip	1/10	
GMS28	50	1.5-2.8	Rubber	Strip	1/10	
GMS38	50	2.7-3.8	Rubber	Strip	1/10	
GMS52	50	3.7-5.2	Rubber	Strip	1/10	
GMS68	50	5.3-6.8	Rubber	Strip	1/10	

CABLE ESSENTIALS

Earthing, Sleeving & Grommets

Heat Shrink

- Material: Polyolefin
- Operating temperature: -55°C to 125°C
- Colour: Black
- Shrink temperature 125°C
- Comes in a handy dispenser box

TLHSK - Heat Shrink (Kit)

Contains 7 popular sizes;

 30pcs 2 x 40mm
 16pcs 7 x 80mm

 25pcs 2.5 x 40mm
 8pcs 10 x 80mm

 20pcs 3.5 x 40mm
 8pcs 13 x 85mm

20pcs 5 x 40mm

Grommets - Black

- Manufactured out of special formula PVC compound
- Designs: Open, Closed and Super
- Available In: 20,25 & 32mm
- Ideal for use in untapped holes of 1.6mm thickness
- Colour: Black

Dimensions

	(mm)				
Code	Dia.	Material	Туре	Box/Qty	per 100
GM20*	20	Rubber	Open	100/10000	
GM25*	25	Rubber	Open	100/5000	
GM32	32	Rubber	Open	100/2000	
GM20B*	20	Rubber	Blind	100/10000	
GM25B*	25	Rubber	Blind	100/5000	
GM32B	32	Rubber	Blind	100/2000	
GM20SUP*	20	Rubber	Super	100/10000	
GM25SUP*	25	Rubber	Super	100/5000	

(*Minimum order quantity 10 boxes)





SCREWS & FIXINGS

Socket Screws & Conduit Box Screws

M3.5 Switch & Socket Screws

- M3.5 raised head slotted screws
- Clearly defined pitch for easy screwing
 Available in nickel steel plated and brass self colour

- Packed in plastic bag of 100
 Range: 25mm to 75mm
 Used with switch & socket boxes



	Dimensior	ns (mm)				
Code	Length	Size	Material	Screw Type	Box/Qty	per 100
S3525NP	25	M3.5	(Nickel Plated)	Standard	100	
S3530NP	30	M3.5	(Nickel Plated)	Standard	100	
S3535NP	35	M3.5	(Nickel Plated)	Standard	100	
S3540NP	40	M3.5	(Nickel Plated)	Standard	100	
S3550NP	50	M3.5	(Nickel Plated)	Standard	100	
S3575NP	75	M3.5	(Nickel Plated)	Standard	100	
S3525B	25	M3.5	(Brass)	Standard	100	
S3535B	35	M3.5	(Brass)	Standard	100	
S3540B	40	M3.5	(Brass)	Standard	100	
S3550B	50	M3.5	(Brass)	Standard	100	
S3560B	60	M3.5	(Brass)	Standard	100	
\$3575B	75	M3 5	(Brace)	Standard .	100	

		Dimension	s (mm)				
Code		Length	Size	Material	Screw Type	Box/Qty	per 100
S48B	С	8	M4	Screw (Brass)	Standard	100	
S410B	С	10	M4	Screw (Brass)	Standard	100	
S412B	С	12	M4	Screw (Brass)	Standard	100	
S416B	С	16	M4	Screw (Brass)	Standard	100	
S420B	С	20	M4	Screw (Brass)	Standard	100	
S425B	С	25	M4	Screw (Brass)	Standard	100	
S435B	С	35	M4	Screw (Brass)	Standard	100	
S440B	С	40	M4	Screw (Brass)	Standard	100	
SASOR	C		M4	Screw (Brass)	Standard	100	



M4 Besa Screws (Brass)

- For the installation of conduit fittings
- Solid brass material
- Bright dipped finish
- Packed in poly bag (100)
- Pan Head slotted screw
- Size 4mm length 6mm 50mm

Extension Screws M3.5 BNP

- Solid brass nickel plated
- For M3.5 machine screws
- Total length 35mm
- Packed in poly bag (100pcs)






	Dimensio	ons (mm)			
Code	Length	Dia.	Head	Box/Qty	per 100
S35ES	35	3.5	Hex	100/1000	

Screws 2BA - Brass

- For the installation of conduit fittings
- Solid brass material
- Bright dipped finish
- Imperial size thread



	Dimensio	ons (mm)			
Code	Length	Туре	Head	Box/Qty	per 100
S2BA34	18.75	2BA	Round	100	
S2BA1	25	2BA	Round	100	
S2BA2	50	2BA	Round	100	



M4 Nuts & Washers (Brass)

- Solid brass nickel plated
- For M3.5 machine screws
- Total length 35mm
- Packed in poly bag (100pcs)

(6

	Dimensi	ons (mm)			
Code	Dia.	Size	Туре	Box/Qty	per 100
S4N	4	M4	Nut (Brass)	100	
S4W	4	M4	Washer (Brass)	100	

M6 Roofing Nuts & Bolts

- Mushroom head, cross slotted.
- Steel bright zinc plated
- and with trunking & cable tray



	Dimensi	ons (mm)			
Code	Length	Size	Bolt/Nut Type	Box/Qty	per 100
S612RNB	12	M6	Roofing	200	
S620RNB	20	M6	Roofing	200	
S625RNB	25	M6	Roofing	200	
S640RNB	40	M6	Roofing	100	
S650RNB	50	M6	Roofing	100	





Capping Nails

- Mickey Pins Capping nails complete with washer
- Ideal for PVC or steel capping
- Available in 25mm and 35mm
- Bright zinc plated
- Heat treated to provide hardness and ductility



 $(\epsilon$

	Dimensio	ons (mm)			
Code	Length	Dia.	Head	Box/Qty	per 100
S25CPN	25	2.5	Countersunk	100/1000	
S35CPN	35	2.5	Countersunk	100/1000	

Channel Spring Nuts

- Mild steel
- Bright zinc plated
- Size: M6, M8, M10
- Suitable for fixing channels
- Spring size: 10mm and 32mm



 $(\epsilon$

	Dimens	sions	Spring/Nut		
Code	Width (mm)	Size	Туре	Box/Qty	per 100
CSN6S	6	M6	Channel/Short	100	
CSN8S	8	M8	Channel/Short	100	
CSN10S	10	M10	Channel/Short	100	
CSN6L	6	M6	Channel/Long	100	
CSN8L	8	M8	Channel/Long	100	
CSN10L	10	M10	Channel/Long	100	





SCREWS & FIXINGS

Screws, Suspension Anchors & Penny Washers

Drywall Screws

- Fully hardened
- Twin thread
- C1022 steelPhillips recess
- Bugle head
- Ideal for plasterboard, fibreboard and other installation boards where these need to be fastened to wood or steel partitions
- Available in fine thread or coarse thread (Black only)
- Bright zinc plating offers a superior anticorrosion treatment which allows water based fillers to be used





	Dimension	S (IIIIII)			
Code	Length	Dia.	Screw Type	Box/Qty	per 100
S3532DWB/Z	32	3.5	Drywall/Phillips	200	
S3538DWB/Z	38	3.5	Drywall/Phillips	200	
S3550DWB/Z	50	3.5	Drywall/Phillips	200	

*Please state finish by adding B for Black Z for Zinc.

Plasterboard Suspension Anchors

- Driva Cavity Drywall Suspension Fixing (Zinc Alloy)
- Self drills into plasterboard for fast installation
- Easy snap-off drill points to permit use where cavity is small or in special application
- Pressure cast zinc alloy anchor body
- Supplied complete with wafer head cross screws
- Screw size: 4mm x 35mm

	Dimension	s (mm)				
Code	Length	Size	Head	Weight	Box/Qty	per 100
SDE	35	4	Cross	741g	100/200	



- Steel bright zinc plated
- Very large outside diameter

	Dimension	is (mm)			
Code	Length	Size	Washer Type	Box/Qty	per 100
S620PW	20	M6	Penny	100	
S625PW	25	M6	Penny	100	
S632PW	32	M6	Penny	100	
S825PW	25	M8	Penny	100	
S832PW	32	M8	Penny	100	
S1025PW	25	M10	Penny	100	
S1032PW	32	M10	Penny	100	



PROFIX ESSENTIALS

CED ELECTRICAL



Wood Screws

- Fully hardened steel
- Twin thread (countersunk screw)
- Shank grips the wood and reduces splitting
- Zinc plated for corrosion protection
- Ideal for hardwood, softwood, chipboard and fibreboard

Brass Round Head

- Manufactured from non-corrosive solid brass
- Single tapered head
- Ideal for use in areas where rusting could be a problem





CSP

Pozi/Drv

Wood Screws & Rawl Plugs

BJR/BLK

Round

BSR Brass



Wood Screws
Countersunk Hardened Twin Head BZP Black JAP Head / Brass Round Head
B: ·



Code	Length (mm)	Length (in)	Size	Туре	Box/Qty	per 1000	per 1000	per 1000
S61	25	1″	6	Wood	200			
S6125	31.25	1.25"	6	Wood	200			
S615	37.5	1.50"	6	Wood	200			
S62	50	2"	6	Wood	200			
S81	25	1"	8	Wood	200			
S8125	31.25	1.25"	8	Wood	200			
S815	37.5	1.5"	8	Wood	200			
S82	50	2"	8	Wood	200			
S83	75	3"	8	Wood	100			
S101	25	1"	10	Wood	200			
S10125	31.25	1.25"	10	Wood	200			
S1015	37.5	1.5"	10	Wood	200			
S102	50	2"	10	Wood	200			
S103	75	3"	10	Wood	100			

- **Note**: Add Suffix to CODE CSP = Countersunk Pozi-Driv
- BSR = Brass Round Head
- BJR = Black JAP Round Head

Expansion Plugs - Plastic (HDPE)

- Manufactured from plastic HDPE
- Two way expansion plugs
- Self centring internal guide
- Temperature range: -20°C to 70°C
- All purpose lightweight fixing

Dimensions (mm)

Code	Length	Dia.	Plug Colour	Box/Qty	per 100
RPYEL	4/6/8	5	Yellow	100/1000	
RPRED	6/8/10	6/6.5	Red	100/1000	
RPBRO	10/12/14	7	Brown	100/1000	







CONDUIT TOOLS

Conduit Bender & Die Sets

Code: CB25

Conduit Bender 20/25mm Vice & Tool Pack (Set) - Hilmor

Sturdy stand (heavy duty) tough and light

- Precision tough aluminium formers
- Easily portable
- Pack consists of 20/25mm bending machine
- O Tool pack 20/25mm & vice and 20/25mm former
- Range of spares accessories available

1140mm 560mm 230mm

LOWEST PRICE

BoxQty 1/12 Each M00: 1

















		Din	nensions (m	nm)			
Code	Pic	Length	Width	Dia.	Spare Type	Box/Qty	Each
CBF20	Α	175	137	-	Former 20mm	1	
CBF25	Α	234	164	-	Former 25mm	1	
CBTS	В	76	31	-	Tube Stop	1	
CBSB	С	186	20	-	Stop Bar	1	
CBCP	D	180	60	-	Centre Pin	1	
CBPV	Ε	170	160	-	Pipe Vice	1	
CBPVJ	F	60	50	-	Pipe Vice Jaws	1	
CBTRP	G	95	62	-	Terry Retaining Pin	1	
CBROLLP	Н	90	-	13	Roller Pin	1	
CBGR	1	60	-	39	Roller/Grooved	1	

CE Approved

PRŒIX

ESSENTIALS



CONDUIT TOOLS

Conduit Bender & Die Sets

BoxQty 1 M00: 1

Code: TAL Hard White Tallow

Used as a lubricant for threading

 Pulling electric cables through conduit (Store between 7-24°C)



Length	Width	Depth
130mm	70mm	90mm

Code: PCGRN

Plastic Compound - Green

- General Purpose Non Hardening Water Resistant Polyurethane Plastic Compound
- Used for sealing fittings in damp situations
- Suitable for wiring Looms & Bulkheads, Conduit or Joint Boxes



Length	Width	Depth
130mm	130mm	100mm



BoxQty 1/25	Each
M00: 1	



BoxQty 1	Each
M00: 1	

Code: DS2025

Conduit Die Set 20mm/25mm "CE" Approved to BS1813

Consists of:-

1 Die stock 1 x 20 x 1 x 25 Guide & Die (Store between 7-24°C



Length	Width	Depth
160mm	100mm	60mm

_	. C	
,	Width	Donth

Length	Width	Depth
160mm	100mm	60mm

Conduit Dies Sets

- Stock, dies and guide made from high quality steel for longer life
- DS20/25 die sets consists of a die stock, 20mm and 25mm set of dies and 20mm and 25mm guides
- Internal dimensions for die stock 42.2 x 17.5mm
- Depth of bore for guides 36.5mm

Dimensions (r	mm
---------------	----

Code	Length	Dia.	Spare Type	Box/Qty	Each
D20	40	20	Conduit (Die)	1	
D25	40	25	Conduit (Die)	1	
DG20	40	20	Conduit (Guide)	1	
DG25	30	25	Conduit (Guide)	1	







TEST INSTRUMENTS

Digital Multi-Meters



Code: CM8050

Digital Clamp Meter 1000v - 53mm Clamp

- Clamp Meter Manual
- 1000v 53mm (Jaw Size) Cat II
- Approval B\$ EN61010-1, CE, LVD | IEC1010-1, CAT | I 1000v
- Supplied with case leads, Batteries and instructions
- Colour Black with Red jaws

Technical Specifications

Jaw Opening: 53mm Ranging: Manual Display: 33/4 digits LCD Peak Data Hold: Yes

AC Current Range: 40A, 400A 1000A (ACA) $\pm (1.5\% + 3dgt)$ Accuracy:

Overload Protection: 1200A (60 sec)

AC Voltage Range: 4dgt)

DC Current Range: Not applicable DC Voltage: Not applicable

Frequency Range: 4kHz, 40kHz, 400kHz, 4000kHz

Accuracy \pm (1.2% + 3dgt)

Code:SCC Combi-Check 1.2 Volt Tester Integrated single pole test phase detection Short response time (<0, 1 second) for fast voltage tests Fully compliant with GS38 Designed and built according to IEC61010, IEC61243-3 Technical Specifications Voltage display 12 - 690 V AC/DC LED resolution 12, 24, 50, 120, 230, 400, 690 LCD resolution 1 V + / - 3 % + 8 digitsVoltage detection Automatic Acoustic signal AC voltage - DC voltage Polarity detection Full range Response time LED < 0.1s, LCD < 2s Frequency range 0 - 400 HzPeak current ls < 0.3 A / ls (after 5s) < 3.5 mAOperation time Recovery time 10 min < 12 V AC/DC DC-1000v AC-750v (ACV) Accuracy \pm (1% + Auto power on Voltage range 100 - 690 V AC Frequency range 50 - 400 HzContinuity $0-400 \text{ K}\Omega$ Measuring range Phase rotation test

100 - 690 V

2 x 1.5 V LR03 batteries

45 - 65 Hz





105g

Voltage range

Power supply

Frequency Over voltage protection

(E 200g

690 V AC/DC g



Code:LM1065

Digital Lux Light Meter

- Safe sealed photo cell for long stability / photo sensor correctly designed in accordance with testing angles and visual sensitivity
- Data hold switch to hold connecting recorder
- Service temperature and humidity: 0~40*C and below 80%RH
- Battery: 9V (006P) 1 pc
- Main unit size and weight: 119 x 64 x 26mm
- Photo sensor size and weight: 125
- Approval: CE, LVD, EMC



Technical Specifications					
Ranges	Allowance	Remarks			
0~200 Lux	4% of rdg / 0.5% of f.s	Color Temperature			
0~000 Lux	4% of rdg / 0.5% of f.s	2856K Corrected			
0~20 000 Lux	7% rdg / 1% of f.s	By standard bulb type AA			

Length	Width	Depth
221mm	62mm	35mm

BoxQty 1/10 Each MOQ: 1

TEST INSTRUMENTS

Digital Light Meters & Insulation Testers



Code:IT509

Digital Insulation Tester

- 3/12" digital LCD displayPolarity indication: Automatically
- polarity "-" display for negative input

 Automatic zero adjustment
- Equipped with continuity test
- Measure high insulation resistance and DC voltage
- Measure high insulation resistance and DC voltage

Functions

- Function keys: Data hold, Max.
- Equipped with a continuity test.
- Measures high insulation resistance with manual range:
 (0.1M£[to 2000M£[)
 250V: 0.1M ~200M 0hm
 500V: 0.1M ~200M 0hm
 1000V:1M ~ 2000M0hm

Measures DC voltage (0V~1000V), AC Voltage (0V~750V).

Technical Specifications					
ACV	Range	Resolution	Accuracy	Input Impedance	Overload Protection
	ACV 750v	1v	+/- (0.8%+4)	10M Ohm	DC 100v AC 750v ms
	DCV 1000v	1v	+/- (0.5%+1)	10M Ohm	DC 100v AC 750v ms
	200M / 250v	0.1M Ohm	. / (20/ + 2)	0.4mA max	
Insulation high resistance	200M / 500v	0.1M Ohm	+/- (3%+3) 0.9r		nA max
	2000M / 1000v	1M 0hm	+/- (3%+5)	1.7mA max	
Continuity Test	0.1 Ohm	<80 0hm	3.3v max	DC/AC 500v / ms	

Length	Width	Depth	BoxQty 1/10	Each
221mm	62mm	35mm	M0Q: 1	





TEST INSTRUMENTS

Multi-Function Testers



Code: MVT-1001

Multi-Function Tester

- 2k/20k 50k ±5% Accuracy
- Type Digital
- Range 2000/20,000/50,000 Lux

 ϵ

BoxQty 1/10 Each M00: 1

Benefits & Features

- Range of voltage and stud testers and cable finder
- Essentials for all electricians
- Useful tools when drilling or chasing walls
- Most products battery operated
- Audible sound made when obstructions or voltages are detected.



Code: DTMVTS75

2 in 1 Metal & Voltage Detector

 Metal-25mm, Voltage - 40mm detector

> ((Each BoxQty 1/20 M0Q: 1



Code: DTMVSTS78

- 3 in 1 Metal/Voltage & Stud
- Metal 25mm Stud 20mm Wood - 10mm





Range - AC 100V~240V

(6 Each BoxQty 1/10 M00: 1



Code: SCM

Check Meter 60Amp Analogue Metal - 25mm Stud - 20mm

Wood - 10mm





Code: VT62-4 Universal Circuit Tester 600V Auto-Voltage Range Detector

 Range - DC 6~400v, AC 6~500v rms

((BoxQty 1/10 Each M00: 1



Code: SCM3P

Credit Meter 3 Phase 80Amp

Metal - 25mm Stud - 20mm Wood - 10mm

 $(\epsilon$ BoxQty 1/10 Each M00: 1

PRŒIX

ESSENTIALS

Important

The UK is the only country in the world to work with Ring Mains, or Final Ring Circuits and without the correct testing equipment and knowledge of procedures it is impossible to tell the difference. It's therefore important to use a tester to ensure that mains in wired correctly.

Our range of ring mains testers are designed to be both simply to use and to ensure your safety. Simply plug them in and they will tell if the mains wiring is faulty.





Code: RMT

Ring Mains Tester



• 3 long life neons indicate the circuit is satisfactorily wired

Designed for easy insertion and removal

BS1363 approval

TOP SELLING

TOP SELLING

I UNIVEST BBIC

 $C \in$

LOWEST PRICE BoxQty 1/10/200 Each 10+ M00: 1



Code: QT

Quick Mains Tester 13Amp

Fits standard UK sockets

- LED indicator to show power connection
- Lid incorporates a 13A fuse
- Tough, plastic construction 16A Rated

	Length	Width				
	130	60				
Code: RMTMS6860A Professional Ring Mains So						
	Clear I ED Indicator of V					

((BoxQty 1/10 Each M00: 1



ocket Tester Black

- Clear LED Indicator of Wiring Errors Including:-
- Missing Earth, Live/Neutral Reverse & Missing Neutral
- Type Tester Cat II, IEC1010-1 600V, Range 240v 50Hz
- BS1363 approval

			LUWEST FRICE
	BoxQtv 1/10	Each	10+
Fits standard UK sockets	M00: 1	Edoli	101



44-48 FRESHWATER ROAD, DAGENHAM, ESSEX RM8 1RX (UK) 020 8503 8500 020 8503 8900 www.cedelectrical.co.uk info@cedelectrical.co.uk